

# ELLI

Esders Laser Leak Indicator



- Colored LCD touch screen
- Selective detection of methane
- Integrated GPS and bluetooth functionality
- User-defined alarm threshold
- Rugged housing design IP54
- Very fast reaction for the detection of smallest amounts of methane
- Detection of methane also by multiple insulating glazing
- Simple, intuitive operation via function keys and touch screen
- No cross sensitivity to other hydrocarbons
- Green laser marker „CLASS 2M“ for optimum visibility measuring range, even in direct sunlight
- Choice of graphical or numerical display of the measured values
- Monitoring of reflection quality by appropriate optical and acoustic indication
- Rechargeable, changeable Li-ion Battery for 8 hours working time
- Video camera for live pictures of background

## PICTURES OF APPLICATION



# ELLI

ELLI is an innovative, portable laser measuring device that can be easily monitor difficult or impossible to reach areas and hazardous areas from a distance.

By the TDLAS (Tunable Diode Laser Absorption Spectroscopy) detection technology, it is possible for the user to determine methane safe from a distance. For this purpose, the laser beam must be directed only to the post to be checked. This detection technology therefore provides a high added value for the user who does not have to enter a potential hazardous area for the inspection of pipelines. Only in the event of a gas leak properly trained staff must be employed by an Identified leak check and seal. Previously it was very difficult and especially time-consuming and costly to detect gas leaks using conventional flame ionization or semiconductor gas detectors. By this significantly reduced verification effort the review of gas leading systems or pipelines is very cost effective compared to conventional verification methods.

## TYPICAL AREAS OF APPLICATION

- Checking of gas lines, for example Pipeline inspection, checking of lines at great heights
- Review of hazardous areas, for example Biogas plants, gas pressure regulating stations
- Recognition of higher methane concentrations in buildings through windows
- Remote check of enclosed gas plants
- Unscheduled testing of underground pipelines

## FUNCTIONALITY

For the inspection of gas lines or fittings the laser beam has to be directed to the inspection area. In this case, the device measures the methane concentration using the difference between the emitted and the received (reflected) infrared laser beam. The wavelength of the laser beam used ensures selective measurement of methane.

## TECHNICAL DATA

Calibration gas	Methane (CH <sub>4</sub> )
Display	Colored LCD touch display
Reaction time	0.1 seconds
Detection method	Tuneable diode laser absorption spectroscopy (TDLAS)
Operating time	8 hours per charge (6 hours charging time)
Power supply	Rechargeable Li-ion Battery
Scanning range	30 m standard, 50 m under good reflection conditions
Weight	1.6 kg
Dimensions	237 x 167 x 74 mm
Measuring range	0 ... 50.000 ppm x m
Temperature range	-17 °C to 50 °C
Humidity	5 to 90 % rel. humidity
Protection class	IP54
Connections	USB, earphone, DC jack, GPS, bluetooth
Data storage	measured values, GPS
Scope of delivery	Earphones, carrying strap, rugged carrying case, charger
Guarantee	24 month
Sensitivity	5 ppm-m at distance 0 ~ 10 m 10 ppm-m at distance 10 ~ 30 m

Technical specifications subject to change! Status 2020/06

