

## OS

## Model 8

The Os-series is a new digital high-speed camera designed to operate in the most demanding environments. The salient design feature of the Os 8 are its compact size combined with a wide data bus, making it capable of achieving very high frame rates (up to 8,000 fps) including transfer speeds to high-capacity solid-state (non-volatile) memory. Configurable DDR options include 16GB and 32GB.

- Optional solid-state, non-volatile memory
- High dynamic range, low noise
- Supports PIV and short-integration modes

### APPLICATIONS

Industrial, R&D, UAV, Laboratory, Media



### KEY FEATURES

Maximum Resolution	1600 x 1200
Maximum FPS @ Maximum Res	8,000 fps
Maximum FPS	194,000 @ 1600 x 16
Streaming Frame Rate	350 fps
Operating Temperature	-40+50°C / -40+122°F

### FRAME PROPERTIES

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 10.4 mm
Sensor Format	1.3 inch
Pixel Size (micron)	8.68 x 8.68 um
Pixel Depth	12 bit mono 36 bit color
Sensitivity	6000 ISO Mono 2000 ISO Color
Min. Exposure Time	1µs (*Shorter Integration optional)
Array	1.9 megapixel
Quantum Efficiency	60%

### MECHANICAL

Weight	0.69 kg or 1.52 lbs
Dimensions	86 x 63 x 88 mm (W x H x L)
Shock & Vibration	Shock: 200G / Vibration: 40G - All axes
Mount	C-Mount (Standard). Manual MFT, Electronic MFT & PL Adapter (Optional).

### IMAGE CAPACITY

DDR	16GB (Standard) - 32GB (Optional)
-----	-----------------------------------

### TRIGGERING AND SYNCHRONIZATION

Sync In	Phase-lock TTL, IEEE1588, 1PPS
Sync Out	Frame sync / Strobe
Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
HDSDI	Optional

### POWER

Input Voltage	24 VDC
Battery	Optional

### COMMUNICATION INTERFACE

Ethernet	1000BaseT
----------	-----------

### EMBEDDED LOGIC

Debayering	Color Cameras Only
Temporal Noise Reduction	Standard
Dynamic Noise Reduction	Standard
User defined ROI's and LUT's	Standard
Frame to frame Auto-Exposure and Motion Trigger	Standard
Mission Mode for Remote/Autonomous Operation	Standard

### SOFTWARE

Motion Inspector	Windows 32/64 - MAC OS X - Apple iOS
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF