

XStream mini

Model HD

The XStream Mini Series HD is a miniature, remote camera head supporting up to a maximum of 1920 x 1080 resolution at 5,350 fps. For easy operation, the camera effortlessly integrates with the XStream RT (available in PCIe or Thunderbolt 3 configurations) for continuous streaming to SSDs in a PC environment, or with IDT's XStream Time Capsule for producing and recording concurrent LIVE and SLOW MOTION playback images. Cameras come standard with a C-mount lens mount but can be optionally configured with a motorized Micro Four Thirds Mount.

- Ultra-compact form factor
- User-Friendly Operation
- Optional Remote Lens Control

APPLICATIONS

Integrative Biology, Range Tracking,
Sports Biomechanics, R&D

KEY FEATURES

Maximum Resolution	1920 x 1080
Maximum FPS @ Maximum Res	5,350 fps
Operating Temperature	-40+50°C / -40+122°F

FRAME PROPERTIES

Sensor Type	CMOS - Proprietary
Sensor Size	17.4 x 12.3 mm (Active)
Sensor Format	1.3 inch
Pixel Size (micron)	9.1 x 9.1 μm
Pixel Depth	10 bit mono 30 bit color
Sensitivity	30,000 ISO Mono, 10,000 ISO Color
Min. Exposure Time	1μs (*Shorter Integration optional)
Array	2 megapixel
Quantum Efficiency	60%

MECHANICAL

Weight	0.20 kg or 0.45 lbs
Dimensions	58 x 47 x 44 mm (W x H x L)
Shock & Vibration	Shock: 200G / Vibration: 40G - All axes
Mount	C-Mount (Standard), Motorized MFT (Optional)



SOFTWARE

Motion Studio	Windows 64
Motion Inspector	Windows 64
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF